

## DECLARATION OF PERFORMANCE

in accordance with Annex 111 of Regulation (EU) No. 305/2011

( Construction Products Regulation )

1. Unique identification code of the product type:

**PRORAPID RS GREY**

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

**Product formulation reference X2004**

3. Intended use as foreseen by the manufacturer of the construction product in accordance with harmonised technical specification:

**Improved fast setting cementitious adhesive with reduced slip**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

**Instarmac Group plc  
Birch Coppice Industrial Estate  
Danny Morson Way, Dordon  
Tamworth B78 1SE  
United Kingdom**

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 ( 2 ):

**Not relevant**

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

**System 3 + 4**

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

**The notified body Ceram, No. 1289 has carried out initial type testing to System 3 and issued Test report No. (124246)-19863**

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued.

**Not relevant**

9. Declared performance

<u>Essential characteristics</u>	<u>Performance</u>	<u>Harmonised technical specification</u>
<b>Bond Strength as:</b>		
Early tensile adhesion	0.7 N/mm <sup>2</sup>	
Initial tensile adhesion	1.9 N/mm <sup>2</sup>	
<b>Durability for tensile Adhesion:</b>		
After heat ageing	1.3 N/mm <sup>2</sup>	
After water immersion	1.2 N/mm <sup>2</sup>	BSEN 12004-1:2017
After freeze/thaw cycles	1.2 N/mm <sup>2</sup>	
<b>Reaction to Fire</b>	<b>Class E WFT</b>	
<b>Release of dangerous Substances</b>	<b>See MSDS</b>	

**CLASSIFICATION - C2FT**

10. The performance of the product identified in items 1 and 2 in conformity with the declared performance set out in item 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for on behalf of the manufacturer by:



..... (Signature)  
Chris Murphy - Technical Director

Tamworth – 21.08.17

..... (Place & Date Issued)

## **DECLARATION OF PERFORMANCE**

in accordance with Annex 111 of Regulation (EU) No. 305/2011

( Construction Products Regulation )

1. Unique identification code of the product type:

**PRORAPID RS WHITE**

2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):

**Product formulation reference X2005**

3. Intended use as foreseen by the manufacturer of the construction product in accordance with harmonised technical specification:

**Improved fast setting cementitious adhesive with reduced slip**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11 (5):

**Instarmac Group plc  
Birch Coppice Industrial Estate  
Danny Morson Way, Dordon  
Tamworth B78 1SE  
United Kingdom**

5. When applicable, the name and contact address of the authorised representative who has received a mandate for the tasks set out in Article 12 ( 2 ):

**Not relevant**

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

**System 3 + 4**

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard:

**The notified body Ceram, No. 1289 has carried out initial type testing to System 3 and issued Test report No.(124246) - 23082**

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued.

**Not relevant**

9. Declared performance

<u>Essential characteristics</u>	<u>Performance</u>	<u>Harmonised technical specification</u>
<b>Bond Strength as:</b>		
<b>Early tensile adhesion</b>	<b>0.6 N/mm<sup>2</sup></b>	
<b>Initial tensile adhesion</b>	<b>2.5 N/mm<sup>2</sup></b>	
<b>Durability for tensile</b>		
<b>Adhesion:</b>		
<b>After heat ageing</b>	<b>1.9 N/mm<sup>2</sup></b>	<b>BSEN 12004-1:2017</b>
<b>After water immersion</b>	<b>1.8 N/mm<sup>2</sup></b>	
<b>After freeze/thaw cycles</b>	<b>1.6 N/mm<sup>2</sup></b>	
<b>Reaction to Fire</b>	<b>Class E WFT</b>	
<b>Release of dangerous</b>		
<b>Substances</b>	<b>See MSDS</b>	

**CLASSIFICATION - C2FT**

10. The performance of the product identified in items 1 and 2 in conformity with the declared performance set out in item 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for on behalf of the manufacturer by:



..... (Signature)  
Chris Murphy - Technical Director

Tamworth – 21.08.17

..... (Place & Date Issued)